



KÖSTER Anti-Slip Granulate 20

Technical Data Sheet CT 411 200

Issued: 2021-12-21

- Various individual test certificates for the slip-resistant properties according to DIN 51130 and DGUV rule 108 003, MPI Asendorf, July 2020, (e.g. for KÖSTER CT 215 Universal Floor, depending on the composition R10, R11 and R12)

Polymer granulate to increase slip resistance of top coating

Features

KÖSTER Anti-Slip Granulate 20 is a chemically resistant polymer granulate, which can be incorporated into aqueous and solvent-free reaction resin top coatings to increase the slip resistance. Depending on the amount added, different classes of slip resistance can be achieved.

Technical Data

Material	Polymer
Color	Transparent
Largest grain size	0,8 mm
Bulk density	0,43 g/cm ³

Fields of Application

KÖSTER Anti-Slip Granulate 20 is incorporated into solvent-free and water-based top coatings like KÖSTER CT 215 Universal Floor or KÖSTER CT 227 1C Silane in various dosages to achieve different slip resistance classes in accordance with DGUV rule 108-103. For further information, please refer to the respective technical data sheets.

Application

Consult the system data sheets for the respective product systems or the technical data sheet for the associated product.

Consumption

2% to 2.5%, depending on required anti-slip category (see System Data Sheet)

The required quantity is a percentage by mass. See technical data sheet for the associated product.

Packaging

CT 411 200	200 g
------------	-------

Storage

Shelf life is a minimum of 2 years when stored dry and pressure-free in the original sealed container.

Safety

Observe all local, state, and federal safety guidelines when processing any material.

Related products

KÖSTER CT 215 Universal Floor	Prod. code CT 215
KÖSTER CT 227 1C Silane	Prod. code CT 227
KÖSTER TS transparent	Prod. code CT 320

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.