



KÖSTER Footpump

Foot operated injection pump for the injection of KÖSTER injection resins

Features

The KÖSTER Foot Pump is a reliable foot driven injection pump which is suited for high pressure injection of all KÖSTER injection resins. It is sturdy, easy to use and easy to clean.

Technical Data

Capacity:	approx. 7.5 cm ³ per pass
Operating pressure:	0 – 200 bar
Measurements:	50 cm x 23 cm x 60 cm
Weight:	approx. 12 kg

Fields of Application

High pressure injection of:

- KÖSTER IN 1
- KÖSTER N 2 / IN 2 HT
- KÖSTER IN 3 / IN 3 HT
- KÖSTER IN 4
- KÖSTER IN 5
- KÖSTER IN 7
- KÖSTER 2IN1
- KÖSTER Mautrol 2C
- KÖSTER Mautrol 2C Flex
- KÖSTER KB-Pox IN

Cleaning

Clean tools immediately after use with KÖSTER Universal Cleaner.

Packaging

IN 958 001 piece

Other

Basic equipment / scope of delivery:

- Manometer 0 - 200 bar
- 6 Liter material hopper
- Lid
- 3 m HD-Material hose with inner diameter 6 mm
- HD-Ball valve with mouthpiece

Related products

KÖSTER IN 1	Prod. code IN 110
KÖSTER 2 IN 1	Prod. code IN 201
KÖSTER IN 2	Prod. code IN 220
KÖSTER IN 3	Prod. code IN 230
KÖSTER KB-Pox IN	Prod. code IN 231
KÖSTER IN 4	Prod. code IN 240
KÖSTER IN 5	Prod. code IN 250
KÖSTER IN 7	Prod. code IN 270

KÖSTER Impact Packer 12	Prod. code IN 903 001
KÖSTER Impact Packer 18 plus	Prod. code IN 904 001
KÖSTER Superpacker	Prod. code IN 915 001
KÖSTER One-Day-Site Packer	Prod. code IN 922 001
KÖSTER HD Injection Hose	Prod. code IN 929 002
KÖSTER Ball Valve	Prod. code IN 929 003
KÖSTER Manometer	Prod. code IN 929 004
KÖSTER Material Hopper	Prod. code IN 929 005
KÖSTER Fine Sieve	Prod. code IN 929 007
KÖSTER Mautrol 2C	Prod. code M 261
KÖSTER Mautrol Flex 2C	Prod. code M 262 020

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.